





NOTES:

- 1). WHEN CUTTING IS REQUIRED, CONTRACTOR SHALL CONFIRM PROPER HEIGHT OF PEDESTAL IS MAINTAINED PRIOR TO CUTTING POLE.
- 2). REFER TO POLE MOUNTING FOR PEDESTRIAN SIGNAL HEADS STANDARD PLATES FOR DETAILS.
- 3). EXTEND THE PEDESTRIAN PATH TO THE VERTICAL PROJECTION LIMIT OF THE PEDESTRIAN PUSHBUTTON WHEN THE PUSHBUTTON IS ONLY ACCESSIBLE FROM A FORWARD APPROACH. THE VERTICAL PROJECTION LIMIT OF THE PEDESTRIAN PUSHBUTTON MAY BE OFFSET FROM THE PEDESTRIAN PATH A MAXIMUM OF 0'-10" FOR ALL OTHER APPLICATIONS.

NOTES:

- 1). PUSHBUTTON ASSEMBLY SHALL BE SECURED TO WOOD POLES WITH 21#2" LAG BOLTS.

	 ENGINEERING SUPPORT RECOMMENDED	PEDESTRIAN PUSHBUTTON LOCATION - PUSHBUTTON ASSEMBLY LOCATION ON POLE				REVIEWED	 DEPUTY DIRECTOR - DESIGN	12/16/2022 DATE
		STANDARD NO. T-18 (2022)	SHT. 1 OF 3	APPROVED	 CHIEF ENGINEER	12/21/2022 DATE		